


ULTRA-PRO® GYPSUM FIBRE PANELS.



ULTRA PRO 100. R



ULTRA PRO 100. SR



ULTRA PRO 150. R



ULTRA PRO 150. SR



ULTRA PRO LOW DECK.

TECHNICAL SPECIFICATIONS.

Standard Dimensions	1000mm x 600mm x 20mm. 900mm x 600mm x 20mm 1200 x 600 x 18mm
Thickness	20mm. 18mm.
Weight	14kg. 16kg. 19.5kg.
Pipe centres	100mm. 150mm. (accommodates 12mm pipe.)
Density	1150kg/m3.
Reaction to fire	A2 (13EN-13501-1.
Swelling after 24hrs contact with water	<2%
BBA Certificate	98/3538.
European Technical approval	ISO 9001. ISO 14001. 2015.

BENIFITS OF OVERLAY PANELS

- ✓ Ease of installation. Improved thermal comfort.
- ✓ Low profile (18mm). Reduces impact on floor heights.
- ✓ Dry Installation accelerates project times.
- ✓ Improves impact and airborne sound.
- ✓ Flexibility for pipe layout.
- ✓ Solid finish.
- ✓ High precision engineered panel.

ULTRA PRO
Clavering, Essex.
CB11 4PW.
TEL: 01799 550222.
Web: www.ultra-pro.co.uk

