

ULTRA-PRO® FLOORJET

ACOUSTIC UNDERLAY



FLOORJET
Acoustic Underlay



FLOORJET RSL
Acoustic Edge Strip

TECHNICAL SPECIFICATIONS

Floorjet Acoustic Underlay Dimensions

Length: 40M
Width: 1250mm (inc. 50mm adhesive overlay strip)
Thickness: 2.5mm

Floorjet RSL Edge Strip Dimensions

Length: 25m
Width: 150mm
Thickness: 8mm

Weight

270g/m²

Damp Proof Membrane

800 gauge polyethylene membrane

Sound Reduction

23dB (BS EN ISO 10140-1 & BS EN ISO 717-2)

BENEFITS OF FLOORJET UNDERLAY

- ✓ High performance acoustic underlay
- ✓ Unrivalled sound reduction performance of 23dB
- ✓ Fully sealed system
- ✓ 0.2mm 800 gauge polyethylene damp proof membrane.
- ✓ 50mm self-adhesive overlay ensure tight bond to adjoining strip
- ✓ Ultra-lightweight 270g/m²
- ✓ High precision engineered

ULTRA PRO
Clavering, Essex.
CB11 4PW.
TEL: 01799 550222.
Web: www.ultra-pro.co.uk

